



# KSI-2400 MONITOR MOUNTING INSTRUCTIONS



The KSI-2400 comes with pre-applied double-sided 3M tape.

The device can be securely mounted to a computer monitor using one of two methods:

**3M Tape Method** — Suitable for most monitor types, including thick and thinner monitors.

**Thumbscrew Method** — Recommended for thinner monitors and laptop screens where stronger adhesion is needed.

For both methods, the device is typically mounted at the **center bottom** or **center top edge** of the monitor, based on the label orientation you ordered. Extra tape is included for reinstallation on a different monitor if necessary.

## 3M TAPE INSTALLATION METHOD

(Recommended for most applications, including thick monitors.)

1. **Remove the bracket** — Unscrew the thumbscrew from the plastic bracket to detach it from the KSI-2400.
2. **Store the bracket** — Reinsert the thumbscrew into the bracket and set the bracket aside for potential future use.
3. **Expose the adhesive** — Peel off the protective cover from the pre-applied 3M tape on the KSI-2400.
4. **Attach the device** — Firmly press the KSI-2400 onto either:
  - The center bottom edge of the monitor, or
  - The center top edge of the monitor.

(Alternatively, you may choose another edge position as preferred.)



## < Center Bottom Installation Shown

**Note:** Ensure the device label orientation matches your chosen mounting position.


# No Tools Needed — Just Peel, Stick, and Protect

# Thumbscrew Ensures a Secure Hold


## THUMBSCREW AND TAPE INSTALLATION

*(Recommended for thin monitors and laptop screens where stronger adhesion is needed.)*

1. **Remove the bracket** — Unscrew the thumbscrew from the plastic bracket to detach it from the KSI-2400.
2. **Prepare the tape**
  - Remove the protective cover from the pre-applied tape on the KSI-2400.
  - Remove the protective cover from the tape on the plastic bracket.
3. **Attach the device** — Firmly press the KSI-2400 onto the monitor edge in the desired mounting position (center bottom edge or center top edge of the monitor) as shown.
4. **Secure the bracket**
  - At the rear of the monitor, place the plastic bracket onto the mounting channel of the KSI-2400 device.
  - Ensure the bracket is flush with the monitor and the tape adheres properly to both the monitor rear surface edge and the KSI-2400.
5. **Tighten the thumbscrew** — Secure the device in place with the thumbscrew as shown.



Peel



Stick



Screw



Protect

Now set your presence  
detection zones. Refer to our online  
PresenceLock™ User Manual for easy setup without software

## KSI Keyboards

14494 Wicks Boulevard, San Leandro, CA 94577  
(510) 562-5000 info@ksikeyboards.com

## FOLLOW US

